



FIBRE based  
solutions

# CERTIFICATE

on the evaluation of recyclability within the paper industry

On the basis of the laboratory analysis and in accordance with the criteria of the PTS method PTS-RH 021:2012 (Draft Oct 2019) the sample described below

---

<b>Product name</b>	<b>Ovenable Barrier paper 120gsm</b>
<b>Product description</b> (Information according to client)	<b>The semi-finished packaging product Ovenable Barrier paper 120gsm is an unprinted, one-side coated paper made of bleached chemical pulp. The base paper (between 118 g/m<sup>2</sup> and 119 g/m<sup>2</sup>) has an one-side coating (between 1 g/m<sup>2</sup> and 2 g/m<sup>2</sup>). The coating material is silicon.</b>
<b>Product category acc. to PTS-RH 021:2012</b>	<b>II – Packaging products as well as paper and board (for the manufacture of packaging products)</b>
<b>Recyclable percentage<sup>1</sup></b>	<b>&gt; 99 %</b>

---

is classified as

**‘Recyclable’**

Within standard stock preparation of the packaging paper industry.

This certificate loses its validity in case of qualitative or quantitative changes of the components of the tested sample and is only applicable in connection with the test report No. AB.0003754-K1 dated 5<sup>th</sup> May 2022.

Heidenau, 19<sup>th</sup> July 2022

Lydia Tempel  
Head of Business Unit  
Smart & Circular Solutions



FIBRE based  
solutions

Mike Schiefer  
Method supervisor

<sup>1</sup> Recyclable percentage (Fibre yield) means the percentage suitable for recycling or usable in papermaking. It corresponds to total mass of the sample (50g oven-dry  $\pm$  100%) minus total reject